BORETOUGH™

AGAVE TRACER WIRE SERIES

Give Us A Call
1.800.690.3408

www.AgaveWire.com

TRACER WIRE FOR EVERY JOB

From draft to dirt, specing BoreTough® tracer wire into your blueprint is the best designation for open trench, directional drilling & pipe bursting operations. All BoreTough® series products provide a strong locating signal which is recognized by UL & ASTM standards for tracer wire applications to ensure consistent reliable performance. Versions are available in 30 volt & 600 volt. Standard packaging: 500, 1000 & 2500 ft put-ups (custom sizes available upon request).





COPPER

Wire Gauge	Coating Thickness
6-18	30 | 45 Mils

FLEXIBLE - CCS

Wire Gauge	Coating Thickness
8-18	30 | 45 Mils

HIGH STRENGTH - CCS

Wire Gauge	Coating Thickness	Break Load
10,12,14	30 | 45 Mils	684, 452, 282 LBS



EXTRA HIGH STRENGTH - CCS

Wire Gauge	Coating Thickness	Break Load
9	45 Mils	1400 LBS
12	45 Mils	1150 LBS



STAINLESS STEEL

Wire Gauge	Coating Thickness	Break Load
3/16	45 Mils	3,700 LBS

AGAVE WIRE LTD
PRODUCTS PROUDLY MANUFACTURED IN THE U.S.A.

Give Us A Call
1.800.690.3408

PRODUCT COMPARISON: COPPER VS CCS

www.AgaveWire.com

Copper Tracer Wire

CCS Tracer Wire



Copper		CCS
Great	FLEXIBILITY	Good
Good	FATIGUE RESISTANCE	Great
Good	CORROSION RESISTANCE	Good
Good	SIGNAL STRENGTH	Good
High	THEFT	Low
Heavy	WEIGHT	10% Lighter
Good	DURABILITY	Great
Low	BREAK LOAD	High
$$$	COST	$

NOTES:

- Copper was the first product used in Tracer applications.
- CCS has been used in Coax since the 1970's and wasn't used in Tracer until the early 2000's as tracer is very comparable to how signal is transmitted in Coax.
- Billions of feet of both Copper & CCS tracer have been used in gas, water & sewer in the last 15 years.
- AC signal is carried on the skin of the wire so the majority of the bare copper is not utilized for tracer applications. This is why cable providers use CCS and the same goes for tracer.